

MATERIAL SAFETY DATA SHEET

Similar to OSHA Form 174

Section I – Manufacturer/Distributor Information

Manufacturer/Distributor Name: W. D. Service Co., Inc.
Address: 780 Creek Road, Bellmawr, NJ 08031
Emergency Telephone Number: 800-424-9300
Chemical Name and Synonyms: Ammonium Hydroxide
Trade Name and Synonyms: Ammonia
Chemical Family: Amine
Formula: NH₄OH
HMIS Hazard Code: Health: 2, Flammability: 0, Reactivity: 0, Other: 0

Section II – Hazardous Ingredients

TLV/PEL
Aqua Ammonia (CAS#1336-21-6) 50 ppm
11.50° Baume 2.5% by weight of ammonia gas dissolved in water

Section III – Physical Data

Boiling Point (F); approx. 186 Specific Gravity: .9859
Vapor Pressure: = Water Volatiles by Weight: 100
Vapor Density: = to Water Evaporation Rate: = to H₂O
Solubility in Water: Complete pH: 12.0
Appearance and Odor: Clear, thin colorless liquid, ammonia odor

Section IV – Fire and Explosion Data

Flash Point: None to Boiling (TOC) Flammable Limits: Not Est.
Extinguishing Media: None. Unusual Fire and Explosion Hazards: Heated material will liberate irritating, toxic and corrosive fumes. Wear self contained breathing apparatus. None: Not Est. = Not Established, Prop. = Proprietary Date Prepared: 11/12/02

Section V – Health Hazard Data

Threshold Limit Value: 50 ppm. Effects of Over Exposure: May be harmful or fatal if swallowed. May cause eye and respiratory irritation. Emergency and first Aid Procedures: For Eyes: Flush with water for at least 15 minutes. If irritation persists, get medical aid. For Skin: Remove contaminated clothing and thoroughly wash affected area. If irritation persists, seek medical aid. If ingested: Give milk, egg white, gelatin, or if none of these are available, water. Do not induce vomiting. Get medical aid, Inhalation: Remove to fresh air. If irritation or difficulty breathing is present, get medical aid. Listed carcinogen, mutagen, teratogen, (ingredient, source, amount): none.

Section VI – Reactivity Data

Stability: Reactive. Conditions to Avoid: Avoid prolonged contact with aluminum and other non-ferrous metals. None
Incompatibility: Avoid contact with all acids and oxidizers. Hazardous Decomposition Products: Varies with contacted Material. May liberate explosive hydrogen gas in contact with non-ferrous metals. Hazardous Polymerization: Will not occur.
Conditions to Avoid: None

Section VII – Spill or Leak Procedures

Steps to Be Taken In Case Material is Spilled or Released: For larger spills: Ventilate area or use ANSI approved Respirators. Recontainerize by Mopping, Wet Vacuum, or Suitable Absorbent. Rinse Remaining Material to Drains. Waste Disposal Method: Follow Local, State, and Federal Regulations.

Section VIII – Special Protection Information

Ventilation: Mechanical, (30 CFM Minimum). Eye Protection: Goggles. Protective gloves: Rubber or latex. Other protective equipment: Use rubber boots if working in a standing solution.

Section IX – Special Precautions

Precautions To Be Taken In Handling and Storage: Store below 100 degrees F.
Other Precautions: Keep Out of Reach of Children. For sale to, use and storage by service personnel only.
THE INFORMATION CONTAINED IN THIS MSDS WAS OBTAINED FROM CURRENT AND RELIABLE SOURCES, HOWEVER, THE DATA IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY, SINCE THE CONDITIONS OF HANDLING, STORAGE AND DISPOSAL OF THIS PRODUCT IS BEYOND THE CONTROL OF THIS COMPANY. IT IS NOT RESPONSIBLE FOR LOSS, INJURY AND EXPENSE ARISING OUT OF THE PRODUCTS IMPROPER USE. NO WARRANTY EXPRESSED OR IMPLIED, REGARDING THE PRODUCT DESCRIBED IN THIS MSDS SHALL BE CREATED OR IMPLIED BY ANY STATEMENT IN THIS MSDS. VARIOUS GOVERNMENT AGENCIES MAY HAVE SPECIFIC REGULATIONS REGARDING THE TRANSPORTATION, HANDLING, STORAGE, USE OR DISPOSAL, OF THIS PRODUCT MAY NOT BE COVERED BY THIS MSDS. THE USER IS RESPONSIBLE FOR FULL COMPLIANCE.